

Package ‘ExclusionTable’

July 21, 2025

Title Creating Tables of Excluded Observations

Version 1.2.0

Description Instead of counting observations before and after a `subset()` call, the `ExclusionTable()` function reports the number before and after each `subset()` call together with the number of observations that have been excluded. This is especially useful in observational studies for keeping track how many observations have been excluded for each in-/ or exclusion criteria. You just need to provide `ExclusionTable()` with a dataset and a list of logical filter statements.

License CC BY 4.0

Encoding UTF-8

URL <https://github.com/entjos/ExclusionTable/>,
<https://entjos.github.io/ExclusionTable/>

BugReports <https://github.com/entjos/ExclusionTable/issues/>

RoxygenNote 7.3.2

Depends R (>= 4.1.0)

Imports cli, data.table

Suggests rmarkdown, knitr, NHANES, remotes, dplyr, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Joshua P. Entrop [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-1614-8096>>),
Simon Steiger [ctb]

Maintainer Joshua P. Entrop <joshuaentrop@posteo.de>

Repository CRAN

Date/Publication 2025-04-06 11:40:02 UTC

Contents

exclusion_table	2
print.exl_tbl	4

Index	5
--------------	----------

exclusion_table	<i>Exclusion Table</i>
-----------------	------------------------

Description

This function keeps track of how many observations you exclude by using specific inclusion and exclusion criteria. It assumes that your criteria are logical filter statements, i.e. statements that you would pass to `dplyr::filter()` or to `{data.table}`.

Usage

```
exclusion_table(
  data = NULL,
  inclusion_criteria = NULL,
  exclusion_criteria = NULL,
  labels_inclusion = inclusion_criteria,
  labels_exclusion = exclusion_criteria,
  obj = NULL,
  keep_data = TRUE,
  id = NULL
)
```

Arguments

- data** A dataframe on which the exclusions are to be performed.
- inclusion_criteria** A character vector of logical expressions that are used for inclusions. All individuals who meet these criteria will be included. Specifically, observations for which the logical expression is `FALSE` will be excluded. Please keep in mind how your expression will handle NA values.
- exclusion_criteria** A character vector of logical expressions that are used for exclusions. All observations who meet this criteria will be excluded. Specifically, observations for which the logical expression is `TRUE` will be excluded. Please keep in mind how your expression will handle NA values.
- labels_inclusion** An optional character vector of labels that are used to label the steps of inclusions. The default labels are the logical expressions passed to `inclusion_criteria`.
- labels_exclusion** An optional character vector of labels that are used to label the steps of exclusions. The default labels are the logical expressions passed to `exclusion_criteria`.

obj	A named list of objects that will be passed to the filtering call. The list can be access using <code>obj\$<name of object></code> in the filtering call.
keep_data	A logical statement to indicate whether the new dataset without the excluded observations should be outputted. The default is TRUE.
id	Optional name of a unique ID variable in the dataset.

Value

`exclusion_table` returns a `exl_tbl` object which is a list of data frames including the following information:

table_in	a <code>data.frame</code> including the number of observations excluded for each inclusion criteria listed in <code>inclusion_criteria</code> .
table_ex	a <code>data.frame</code> including the number of observations excluded for each exclusion criteria listed in <code>exclusion_criteria</code> .
dataset	a <code>data.frame</code> of the supplied dataset after applying all inclusion and exclusion criteria.

If `id` is supplied, an additional column is added to `table_in` and `table_ex` including a list of the IDs that have been excluded from the dataset in each step.

Examples

```
#Example without using the obj argument
exclusion_table(
  data = mtcars,
  exclusion_criteria = c("disp <= 70 | disp >= 300",
                        "as.character(gear) == '4'"),
  labels_exclusion = c("First exclusion",
                     "Second exclusion")
)
```

```
#Example using the obj argument
my_selection <- c(8, 6)

exclusion_table(
  data = mtcars,
  exclusion_criteria = c("cyl %in% my_selection"),
  labels_exclusion = c("First exclusion"),
  obj = list(my_selection = my_selection)
)
```

print.ex1_tbl	<i>Prints ex1_tbl objects</i>
---------------	-------------------------------

Description

This is a print function for ex1_tbl objects, created with `exlcusion_table()`. The function improves the readability of the output.

Usage

```
## S3 method for class 'ex1_tbl'  
print(x, ...)
```

Arguments

x	An ex1_tbl object.
...	Other arguments that should be passed to print.

Value

No return value, called for side effects.

Index

`exclusion_table`, 2

`print.exl_tbl`, 4