

Package ‘hce’

July 11, 2025

Type Package

Title Design and Analysis of Hierarchical Composite Endpoints

Version 0.8.0

Description Simulate and analyze hierarchical composite endpoints. Includes implementation for the kidney hierarchical composite endpoint as defined in Heerspink HL et al (2023) “Development and validation of a new hierarchical composite endpoint for clinical trials of kidney disease progression” (Journal of the American Society of Nephrology 34 (2): 2025–2038, <[doi:10.1681/ASN.000000000000243](https://doi.org/10.1681/ASN.000000000000243)>). Win odds, also called Wilcoxon-Mann-Whitney or success odds, is the main analysis method. Other win statistics (win probability, win ratio, net benefit) are also implemented in the univariate case, provided there is no censoring. The win probability analysis is based on the Brunner-Munzel test and uses the DeLong-DeLong-Clarke-Pearson variance estimator, as described by Brunner and Konietzschke (2025) in “An unbiased rank-based estimator of the Mann-Whitney variance including the case of ties” (Statistical Papers 66 (1): 20, <[doi:10.1007/s00362-024-01635-0](https://doi.org/10.1007/s00362-024-01635-0)>). Stratification and covariate adjustment are performed based on the methodology presented by Koch GG et al. in “Issues for covariance analysis of dichotomous and ordered categorical data from randomized clinical trials and non-parametric strategies for addressing them” (Statistics in Medicine 17 (15-16): 1863–92). For a review, see Gasparyan SB et al (2021) “Adjusted win ratio with stratification: Calculation methods and interpretation” (Statistical Methods in Medical Research 30 (2): 580–611, <[doi:10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558)>).

License MIT + file LICENSE

Depends R (>= 3.5)

Imports base, stats

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Samvel B. Gasparyan [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-4797-2208>>)

Maintainer Samvel B. Gasparyan <gasparyan.co@gmail.com>

Repository CRAN

Date/Publication 2025-07-11 15:00:02 UTC

Contents

ADET	3
ADLB	4
ADSL	5
as_hce	5
as_hce.data.frame	6
as_hce.default	7
calcWINS	7
calcWINS.data.frame	8
calcWINS.formula	11
calcWINS.hce	13
calcWO	15
calcWO.data.frame	16
calcWO.formula	17
calcWO.hce	18
COVID19	20
COVID19b	20
COVID19plus	21
hce	22
HCE1	23
HCE2	24
HCE3	24
HCE4	25
IWP	26
KHCE	27
minWO	28
plot.hce	29
plot.hce_results	30
powerWO	30
print.hce_results	32
propWINS	33
regWO	34
regWO.data.frame	35
regWO.formula	36
simHCE	38
simKHCE	40
simORD	42
sizeWO	43
sizeWR	45
stratWO	46
stratWO.data.frame	47
summaryWO	49

<i>ADET</i>	3
summaryWO.data.frame	49
summaryWO.formula	50
summaryWO.hce	51
Index	52

ADET	<i>Event-Time dataset for kidney outcomes.</i>
------	--

Description

A dataset with multiple kidney outcomes over time scale outcomes of 1500 patients in the ADSL dataset.

Usage

ADET

Format

a data frame with 604 rows (events) and 6 variables:

ID patient identifiers, numeric

AVAL occurrence time of the event, numeric

PARAM name of the event, character

PARAMCD coded name of the event, character

PARAMN type of the event, outcomes 1-7, where a higher value means a better outcome, numeric

TRTPN treatment values, 1 Active or 2 Placebo, numeric

Source

Heerspink HL et al "Development and validation of a new hierarchical composite endpoint for clinical trials of kidney disease progression." Journal of the American Society of Nephrology (2023): [doi:10.1681/ASN.000000000000243](https://doi.org/10.1681/ASN.000000000000243).

Examples

```
head(ADET)
# Number of unique patients
length(unique(ADET$ID))
# Number of events per event type
barplot(table(ADET$PARAM))
```

ADLB	<i>Laboratory dataset for Glomerular Filtration Rate (GFR) measurements.</i>
------	--

Description

A dataset of laboratory measurements of kidney function over time for the 1500 patients in the ADSL dataset.

Usage

ADLB

Format

a data frame with 13980 rows and 8 variables:

ID patient identifiers, numeric

TRTPN treatment values, 1 Active or 2 Placebo, numeric

AVAL measurement value, numeric

ADAY measurement day in the study, numeric

AVISITN hospital visit number, numeric

PARAM name of the event, GFR measurements, character

PARAMCD coded name of the event, GFR, character

PARAMN type of the event is set to 7 for all measurements, numeric

Source

Heerspink HL et al "Development and validation of a new hierarchical composite endpoint for clinical trials of kidney disease progression." Journal of the American Society of Nephrology (2023): [doi:10.1681/ASN.000000000000243](https://doi.org/10.1681/ASN.000000000000243).

Examples

```
head(ADLB)
```

ADSL	<i>Baseline characteristics dataset of patients with kidney function assessments.</i>
------	---

Description

A data frame with baseline characteristics for 1500 patients used to derive KHCE dataset.

Usage

ADSL

Format

a data frame with 1500 rows and 4 variables:

ID patient identifiers, numeric

TRTPN treatment values, 1 Active or 2 Placebo, numeric

EGFRBL Baseline GFR values of patients, numeric

STRATAN strata 1-4, higher value means a higher risk for kidney disease progression, numeric

Source

Heerspink HL et al "Development and validation of a new hierarchical composite endpoint for clinical trials of kidney disease progression." *Journal of the American Society of Nephrology* (2023): [doi:10.1681/ASN.000000000000243](https://doi.org/10.1681/ASN.000000000000243).

Examples

```
head(ADSL)
```

as_hce	<i>A generic function for coercing data structures to hce objects</i>
--------	---

Description

A generic function for coercing data structures to hce objects

Usage

```
as_hce(x, ...)
```

Arguments

x an object used to select a method.

... additional parameters.

Value

an hce object.

See Also

[as_hce.data.frame\(\)](#).

Examples

```
### data frames
data(HCE1)
HCE <- as_hce(HCE1)
calcWINS(HCE)
```

as_hce.data.frame	<i>Coerce a data frame to an hce object</i>
-------------------	---

Description

Coerce a data frame to an hce object

Usage

```
## S3 method for class 'data.frame'
as_hce(x, ...)
```

Arguments

x	a data frame.
...	additional parameters.

Value

an hce object.

See Also

[as_hce\(\)](#), [as_hce.default\(\)](#).

Examples

```
KHCE <- as_hce(KHCE)
calcWO(KHCE)
```

as_hce.default	<i>Coerce a data frame to an hce object</i>
----------------	---

Description

Coerce a data frame to an hce object

Usage

```
## Default S3 method:  
as_hce(x, ...)
```

Arguments

x	an object.
...	additional parameters.

Value

an hce object.

See Also

[as_hce\(\)](#), [as_hce.data.frame\(\)](#).

Examples

```
dat <- KHCE  
class(dat) <- "moo" # non-existent class  
as_hce(dat) # tries to convert to an hce object
```

calcWINS	<i>A generic function for calculating win statistics</i>
----------	--

Description

A generic function for calculating win statistics

Usage

```
calcWINS(x, ...)
```

Arguments

x	an object used to select a method.
...	further arguments passed to or from other methods.

Value

a data frame containing calculated values.

See Also

[calcWINS.hce\(\)](#), [calcWINS.formula\(\)](#), [calcWINS.data.frame\(\)](#) methods.

calcWINS.data.frame *Win statistics calculation using a data frame*

Description

Win statistics calculation using a data frame

Usage

```
## S3 method for class 'data.frame'
calcWINS(
  x,
  AVAL,
  TRTP,
  ref,
  alpha = 0.05,
  WOnull = 1,
  SE_WP_Type = c("biased", "unbiased"),
  ...
)
```

Arguments

x	a data frame containing subject-level data.
AVAL	variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
ref	the reference treatment group.
alpha	2-sided significance level. The default is 0.05.
WOnull	the null hypothesis. The default is 1.
SE_WP_Type	biased or unbiased standard error for win probability. The default is biased.
...	additional parameters.

Details

When `SE_WP_Type = "unbiased"`, the calculations for win proportion, net benefit, and win odds utilize the unbiased standard error from Brunner-Konietschke (2025) paper which is a reformulation of the original formula proposed by Bamber (1975).

Value

a list containing win statistics and their confidence intervals. It contains the following named data frames:

- summary a data frame containing number of wins, losses, and ties of the active treatment group and the overall number of comparisons.
- WP a data frame containing the win probability and its confidence interval.
- NetBenefit a data frame containing the net benefit and its confidence interval. This is just a $2x-1$ transformation of WP and its CI.
- WO a data frame containing the win odds and its confidence interval.
- WR1 a data frame containing the win ratio and its confidence interval, using the transformed standard error of the gamma statistic.
- WR2 a data frame containing the win ratio and its confidence interval, using the standard error calculated using P_{ties} .
- gamma a data frame containing Goodman Kruskal's gamma and its confidence interval.
- SE a data frame containing standard errors used to calculate the Confidence intervals for win statistics.

References

The theory of win statistics is covered in the following papers:

- Win proportion and win odds confidence interval calculation:

Bamber D (1975) "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4: 387-415. doi:[10.1016/0022-2496\(75\)90001-2](https://doi.org/10.1016/0022-2496(75)90001-2).

DeLong ER et al. (1988) "Comparing the Areas Under Two or More Correlated Receiver Operating Characteristic Curves: A Nonparametric Approach." *Biometrics* 44.3: 837-845. doi:[10.2307/2531595](https://doi.org/10.2307/2531595).

Brunner E et al. (2021) "Win odds: an adaptation of the win ratio to include ties." *Statistics in Medicine* 40.14: 3367-3384. doi:[10.1002/sim.8967](https://doi.org/10.1002/sim.8967).

Gasparian SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558).

Gasparian SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. doi:[10.1080/10543406.2021.1968893](https://doi.org/10.1080/10543406.2021.1968893).

Brunner E, Konietschke F. (2025) "An unbiased rank-based estimator of the Mann-Whitney variance including the case of ties." *Statistical Papers* 66.20. doi:[10.1007/s00362-024-01635-0](https://doi.org/10.1007/s00362-024-01635-0).

- Win ratio: the first CI utilizes the standard error derived from the gamma statistic standard error as outlined by:

Gasparyan SB, Kowalewski EK, Buenconsejo J, Koch GG. (2023) "Hierarchical Composite Endpoints in COVID-19: The DARE-19 Trial." In Case Studies in Innovative Clinical Trials, Chapter 7, 95–148. Chapman; Hall/CRC. doi:10.1201/9781003288640-7.

- Win ratio: the second CI utilizes the standard error presented by:

Yu RX, Ganju J. (2022) "Sample size formula for a win ratio endpoint." Statistics in Medicine 41.6: 950-63. doi:10.1002/sim.9297.

- Goodman Kruskal's gamma and CI: matches implementation in DescTools::GoodmanKruskalGamma() and based on:

Agresti A. (2002) Categorical Data Analysis. John Wiley & Sons, pp. 57-59. doi:10.1002/0471249688.

Brown MB, Benedetti JK. (1977) "Sampling Behavior of Tests for Correlation in Two-Way Contingency Tables." Journal of the American Statistical Association 72, 309-315. doi:10.1080/01621459.1977.10480995.

Goodman LA, Kruskal WH. (1954) "Measures of association for cross classifications." Journal of the American Statistical Association 49, 732-764. doi:10.1080/01621459.1954.10501231.

Goodman LA, Kruskal WH. (1963) "Measures of association for cross classifications III: Approximate sampling theory." Journal of the American Statistical Association 58, 310-364. doi:10.1080/01621459.1963.10500850.

See Also

`calcWINS()`, `calcWINS.hce()`, `calcWINS.formula()`.

Examples

```
calcWINS(x = COVID19b, AVAL = "GROUP", TRTP = "TRTP", ref = "Placebo")
## Biased vs unbiased
n0 <- 5; n1 <- 7; p0 <- 0.2; p1 <- 0.5; x <- 1:20; delta <- 0.5
WP0 <- (p1 - p0)/2 + 0.5
DAT <- NULL
for(i in x){
  dat <- data.frame(AVAL = c(rbinom(n1, size = 1, p1), rbinom(n0, size = 1, p0)),
    TRTP = c(rep("A", n1), rep("P", n0)))
  CL1 <- calcWINS(x = dat, AVAL = "AVAL", TRTP = "TRTP", ref = "P")$WP
  CL1$Type <- "biased"
  CL2 <- calcWINS(x = dat, AVAL = "AVAL", TRTP = "TRTP",
    ref = "P", SE_WP_Type = "unbiased")$WP
  CL2$Type <- "unbiased"
  DAT <- rbind(DAT, CL1, CL2)
}
WP <- DAT$WP[DAT$Type == "unbiased"]
```

```

plot(x, WP, pch = 19, xlab = "Simulations", ylab = "Win Probability", ylim = c(0., 1.1))
points(x + delta, WP, pch = 19)
arrows(x, DAT$LCL[DAT$Type == "unbiased"],
       x, DAT$UCL[DAT$Type == "unbiased"], angle = 90, code = 3, length = 0.05, "green")
arrows(x + delta, DAT$LCL[DAT$Type == "biased"],
       x + delta, DAT$UCL[DAT$Type == "biased"], angle = 90, code = 3, length = 0.05, col = "red")
abline(h = c(WP0, 1), col = "blue", lty = 3)
legend("bottomleft", legend = c("True WP", "Biased", "Unbiased"),
      col = c(4, 2, 3), lty = c(3, 1, 1), cex = 0.75)

```

calcWINS.formula	<i>Win statistics calculation using formula syntax</i>
------------------	--

Description

Win statistics calculation using formula syntax

Usage

```

## S3 method for class 'formula'
calcWINS(x, data, ...)

```

Arguments

x	an object of class formula.
data	a data frame.
...	additional parameters.

Value

a list containing win statistics and their confidence intervals. It contains the following named data frames:

- summary a data frame containing number of wins, losses, and ties of the active treatment group and the overall number of comparisons.
- WP a data frame containing the win probability and its confidence interval.
- NetBenefit a data frame containing the net benefit and its confidence interval. This is just a $2x-1$ transformation of WP and its CI.
- WO a data frame containing the win odds and its confidence interval.
- WR1 a data frame containing the win ratio and its confidence interval, using the transformed standard error of the gamma statistic.
- WR2 a data frame containing the win ratio and its confidence interval, using the standard error calculated using P_{ties} .
- gamma a data frame containing Goodman Kruskal's gamma and its confidence interval.
- SE a data frame containing standard errors used to calculate the Confidence intervals for win statistics.

References

The theory of win statistics is covered in the following papers:

- Win proportion and win odds confidence interval calculation:

Bamber D (1975) "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4: 387-415. doi:[10.1016/0022-2496\(75\)90001-2](https://doi.org/10.1016/0022-2496(75)90001-2).

DeLong ER et al. (1988) "Comparing the Areas Under Two or More Correlated Receiver Operating Characteristic Curves: A Nonparametric Approach." *Biometrics* 44.3: 837-845. doi:[10.2307/2531595](https://doi.org/10.2307/2531595).

Brunner E et al. (2021) "Win odds: an adaptation of the win ratio to include ties." *Statistics in Medicine* 40.14: 3367-3384. doi:[10.1002/sim.8967](https://doi.org/10.1002/sim.8967).

Gasparyan SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558).

Gasparyan SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. doi:[10.1080/10543406.2021.1968893](https://doi.org/10.1080/10543406.2021.1968893).

Brunner E, Konietschke F. (2025) "An unbiased rank-based estimator of the Mann–Whitney variance including the case of ties." *Statistical Papers* 66.20. doi:[10.1007/s00362-024-01635-0](https://doi.org/10.1007/s00362-024-01635-0).

- Win ratio: the first CI utilizes the standard error derived from the gamma statistic standard error as outlined by:

Gasparyan SB, Kowalewski EK, Buenconsejo J, Koch GG. (2023) "Hierarchical Composite Endpoints in COVID-19: The DARE-19 Trial." In *Case Studies in Innovative Clinical Trials*, Chapter 7, 95–148. Chapman; Hall/CRC. doi:[10.1201/9781003288640-7](https://doi.org/10.1201/9781003288640-7).

- Win ratio: the second CI utilizes the standard error presented by:

Yu RX, Ganju J. (2022) "Sample size formula for a win ratio endpoint." *Statistics in Medicine* 41.6: 950-63. doi:[10.1002/sim.9297](https://doi.org/10.1002/sim.9297).

- Goodman Kruskal's gamma and CI: matches implementation in DescTools::GoodmanKruskalGamma() and based on:

Agresti A. (2002) *Categorical Data Analysis*. John Wiley & Sons, pp. 57-59. doi:[10.1002/0471249688](https://doi.org/10.1002/0471249688).

Brown MB, Benedetti JK. (1977) "Sampling Behavior of Tests for Correlation in Two-Way Contingency Tables." *Journal of the American Statistical Association* 72, 309-315. doi:[10.1080/01621459.1977.10480995](https://doi.org/10.1080/01621459.1977.10480995).

Goodman LA, Kruskal WH. (1954) "Measures of association for cross classifications." *Journal of the American Statistical Association* 49, 732-764. doi:[10.1080/01621459.1954](https://doi.org/10.1080/01621459.1954).

10501231.

Goodman LA, Kruskal WH. (1963) "Measures of association for cross classifications III: Approximate sampling theory." Journal of the American Statistical Association 58, 310-364. doi:10.1080/01621459.1963.10500850.

See Also

[calcWINS\(\)](#), [calcWINS.hce\(\)](#), [calcWINS.data.frame\(\)](#).

Examples

```
# Example 1
calcWINS(x = GROUP ~ TRTP, data = COVID19b)
# Example 2
calcWINS(x = GROUP ~ TRTP, data = COVID19, ref = "Placebo", alpha = 0.01, WOnull = 1.2)
#' Example 3
calcWINS(x = GROUP ~ TRTP, data = COVID19)$WP
calcWINS(x = GROUP ~ TRTP, data = COVID19, SE_WP_Type = "unbiased")$WP
```

calcWINS.hce

Win statistics calculation for hce objects

Description

Win statistics calculation for hce objects

Usage

```
## S3 method for class 'hce'
calcWINS(x, ...)
```

Arguments

x an hce object.
... additional parameters.

Value

a list containing win statistics and their confidence intervals. It contains the following named data frames:

- summary a data frame containing number of wins, losses, and ties of the active treatment group and the overall number of comparisons.
- WP a data frame containing the win probability and its confidence interval.
- NetBenefit a data frame containing the net benefit and its confidence interval. This is just a $2x-1$ transformation of WP and its CI.
- WO a data frame containing the win odds and its confidence interval.

- WR1 a data frame containing the win ratio and its confidence interval, using the transformed standard error of the gamma statistic.
- WR2 a data frame containing the win ratio and its confidence interval, using the standard error calculated using P_{ties} .
- gamma a data frame containing Goodman Kruskal's gamma and its confidence interval.
- SE a data frame containing standard errors used to calculate the Confidence intervals for win statistics.

References

The theory of win statistics is covered in the following papers:

- Win proportion and win odds confidence interval calculation:

Bamber D (1975) "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4: 387-415. doi:10.1016/0022-2496(75)90001-2.

DeLong ER et al. (1988) "Comparing the Areas Under Two or More Correlated Receiver Operating Characteristic Curves: A Nonparametric Approach." *Biometrics* 44.3: 837-845. doi:10.2307/2531595.

Brunner E et al. (2021) "Win odds: an adaptation of the win ratio to include ties." *Statistics in Medicine* 40.14: 3367-3384. doi:10.1002/sim.8967.

Gasparyan SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:10.1177/0962280220942558.

Gasparyan SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. doi:10.1080/10543406.2021.1968893.

Brunner E, Konietschke F. (2025) "An unbiased rank-based estimator of the Mann-Whitney variance including the case of ties." *Statistical Papers* 66.20. doi:10.1007/s00362-024-01635-0.

- Win ratio: the first CI utilizes the standard error derived from the gamma statistic standard error as outlined by:

Gasparyan SB, Kowalewski EK, Buenconsejo J, Koch GG. (2023) "Hierarchical Composite Endpoints in COVID-19: The DARE-19 Trial." In *Case Studies in Innovative Clinical Trials*, Chapter 7, 95-148. Chapman; Hall/CRC. doi:10.1201/9781003288640-7.

- Win ratio: the second CI utilizes the standard error presented by:

Yu RX, Ganju J. (2022) "Sample size formula for a win ratio endpoint." *Statistics in Medicine* 41.6: 950-63. doi:10.1002/sim.9297.

- Goodman Kruskal's gamma and CI: matches implementation in DescTools: :GoodmanKruskalGamma() and based on:

Agresti A. (2002) Categorical Data Analysis. John Wiley & Sons, pp. 57-59. doi:10.1002/0471249688.

Brown MB, Benedetti JK. (1977) "Sampling Behavior of Tests for Correlation in Two-Way Contingency Tables." Journal of the American Statistical Association 72, 309-315. doi:10.1080/01621459.1977.10480995.

Goodman LA, Kruskal WH. (1954) "Measures of association for cross classifications." Journal of the American Statistical Association 49, 732-764. doi:10.1080/01621459.1954.10501231.

Goodman LA, Kruskal WH. (1963) "Measures of association for cross classifications III: Approximate sampling theory." Journal of the American Statistical Association 58, 310-364. doi:10.1080/01621459.1963.10500850.

See Also

`calcWINS()`, `calcWINS.formula()`, `calcWINS.data.frame()`.

Examples

```
# Example 1
COVID19HCE <- hce(GROUP = COVID19$GROUP, TRTP = COVID19$TRTP)
calcWINS(COVID19HCE)
# Example 2
COVID19bHCE <- hce(GROUP = COVID19b$GROUP, TRTP = COVID19b$TRTP)
calcWINS(COVID19bHCE, ref = "Placebo", WOnull = 1.1, alpha = 0.01)
# Example 3
calcWINS(COVID19HCE, SE_WP_Type = "unbiased")$WP
calcWINS(COVID19HCE, SE_WP_Type = "biased")$WP
```

calcWO

A generic function for calculating win odds

Description

A generic function for calculating win odds

Usage

```
calcWO(x, ...)
```

Arguments

x an object used to select a method.
 ... further arguments passed to or from other methods.

Value

a data frame containing calculated values.

See Also

`calcWO.hce()`, `calcWO.formula()`, `calcWO.data.frame()` methods.

calcWO.data.frame	<i>Win odds calculation using a data frame</i>
-------------------	--

Description

Win odds calculation using a data frame

Usage

```
## S3 method for class 'data.frame'
calcWO(x, AVAL, TRTP, ref, alpha = 0.05, WOnull = 1, ...)
```

Arguments

x	a data frame containing subject-level data.
AVAL	variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
ref	the reference treatment group.
alpha	significance level. The default is 0.05.
WOnull	the null hypothesis. The default is 1.
...	additional parameters.

Value

a data frame containing the win odds and its confidence interval. It contains the following columns:

- WO calculated win odds.
- LCL lower confidence limit.
- UCL upper confidence limit.
- SE standard error of the win odds.
- WOnull win odds of the null hypothesis (specified in the WOnull argument).
- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- WP calculated win probability.
- LCL_WP lower confidence limit for WP.

- UCL_WP upper confidence limit for WP.
- SE_WP standard error of the win probability.
- SD_WP standard deviation of the win probability, calculated as SE_WP multiplied by sqrt(N).
- N total number of patients in the analysis.

References

Gasparyan SB et al. "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2 (2021): 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558)

See Also

[calcWO\(\)](#), [calcWO.hce\(\)](#), [calcWO.formula\(\)](#).

Examples

```
data(HCE4)
calcWO(x = HCE4, AVAL = "AVAL", TRTP = "TRTP", ref = "P")
```

<code>calcWO.formula</code>	<i>Win odds calculation using formula syntax</i>
-----------------------------	--

Description

Win odds calculation using formula syntax

Usage

```
## S3 method for class 'formula'
calcWO(x, data, ...)
```

Arguments

<code>x</code>	an object of class <code>formula</code> .
<code>data</code>	a data frame.
<code>...</code>	additional parameters.

Value

a data frame containing the win odds and its confidence interval. It contains the following columns:

- WO calculated win odds.
- LCL lower confidence limit.
- UCL upper confidence limit.
- SE standard error of the win odds.
- WOnull win odds of the null hypothesis (specified in the `WOnull` argument).

- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- WP calculated win probability.
- LCL_WP lower confidence limit for WP.
- UCL_WP upper confidence limit for WP.
- SE_WP standard error of the win probability.
- SD_WP standard deviation of the win probability, calculated as SE_WP multiplied by sqrt(N).
- N total number of patients in the analysis.
- formula returning the specified formula in the x argument.
- ref showing how the reference group was selected. Can be modifying by specifying the ref argument.

References

Gasparyan SB et al. "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2 (2021): 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558)

See Also

[calcWO\(\)](#), [calcWO.hce\(\)](#), [calcWO.data.frame\(\)](#).

Examples

```
#Example 1
data(HCE1)
calcWO(AVAL ~ TRTP, data = HCE1)

#Example 2
calcWO(GROUP ~ TRTP, data = COVID19, ref = "Placebo", alpha = 0.01)
```

calcWO.hce

Win odds calculation for hce objects

Description

Win odds calculation for hce objects

Usage

```
## S3 method for class 'hce'
calcWO(x, ...)
```

Arguments

x an hce object.
... additional parameters.

Value

a data frame containing the win odds and its confidence interval. It contains the following columns:

- WO calculated win odds.
- LCL lower confidence limit.
- UCL upper confidence limit.
- SE standard error of the win odds.
- WOnull win odds of the null hypothesis (specified in the WOnull argument).
- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- WP calculated win probability.
- LCL_WP lower confidence limit for WP.
- UCL_WP upper confidence limit for WP.
- SE_WP standard error of the win probability.
- SD_WP standard deviation of the win probability, calculated as SE_WP multiplied by sqrt(N).
- N total number of patients in the analysis.

References

Gasparyan SB et al. "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2 (2021): 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558)

See Also

[calcWO\(\)](#), [calcWO.formula\(\)](#), [calcWO.data.frame\(\)](#).

Examples

```
Rates_A <- c(1, 1.5)
Rates_P <- c(2, 2)
dat <- simHCE(n = 500, TTE_A = Rates_A, TTE_P = Rates_P, CM_A = 1.25, CM_P = 1)
calcWO(dat)
calcWO(dat, ref = "A", WOnull = 1, alpha = 0.01)
```

 COVID19

COVID-19 ordinal scale dataset (full report).

Description

A dataset with COVID-19 ordinal scale outcomes for 1062 patients.

Usage

COVID19

Format

a data frame with 1062 rows and 2 variables:

GROUP type of the event, ordinal outcomes 1-8, where a higher value means a better outcome

TRTP treatment values, A Active or P Placebo, character

Source

Beigel JH et al. "Remdesivir for the treatment of Covid-19-final report." New England Journal of Medicine 383.19 (2020): 1813-1836. [doi:10.1056/NEJMoa2007764](https://doi.org/10.1056/NEJMoa2007764).

Examples

```
#Frequencies
table(COVID19)
mosaicplot(table(COVID19), col = c(1, 8, 6, 2, 4, 5, 3, 7),
xlab = "Treatment", ylab = "Ordinal Scale", main = "COVID-19 ordinal scale")
# Convert to an hce object
COVID19HCE <- hce(GROUP = COVID19$GROUP, TRTP = COVID19$TRTP)
# Summary wins, losses, and ties with win odds
summaryWO(COVID19HCE, ref = "Placebo")
```

 COVID19b

COVID-19 ordinal scale dataset (preliminary report).

Description

A dataset with COVID-19 ordinal scale outcomes for 844 patients.

Usage

COVID19b

Format

a data frame with 844 rows and 2 variables:

GROUP type of the event, ordinal outcomes 1-8, where a higher value means a better outcome

TRTP treatment values, Active or Placebo, character

Source

Beigel JH et al. "Remdesivir for the treatment of Covid-19-final report." New England Journal of Medicine 383.19 (2020): 1813-1836. doi:[10.1056/NEJMoa2007764](https://doi.org/10.1056/NEJMoa2007764).

Examples

```
#Frequencies
table(COVID19b)
mosaicplot(table(COVID19b), col = c(1, 8, 6, 2, 4, 5, 3, 7),
xlab = "Treatment", ylab = "Ordinal Scale", main = "COVID-19 ordinal scale")
# Calculate win statistics
calcWINS(x = COVID19b, AVAL = "GROUP", TRTP = "TRTP", ref = "Placebo")
```

COVID19plus

COVID-19 ordinal scale dataset for a combination therapy.

Description

A dataset with COVID-19 ordinal scale outcomes for 1033 patients.

Usage

COVID19plus

Format

a data frame with 1033 rows and 4 variables:

ID patient identifiers, numeric

TRTP treatment values, A Active or P Placebo, character

GROUP type of the event, ordinal outcomes 1-8, where a higher value means a better outcome

BASE baseline ordinal values

Source

Kalil AC et al. "Baricitinib plus Remdesivir for Hospitalized Adults with Covid-19." New England Journal of Medicine 384.9 (2021): 795-807. doi:[10.1056/NEJMoa2031994](https://doi.org/10.1056/NEJMoa2031994).

Examples

```
COVID19HCE <- hce(GROUP = COVID19plus$GROUP, TRTP = COVID19plus$TRTP)
# Summary wins, losses, and ties with win odds
summaryWO(COVID19HCE, ref = "P")
```

hce

Helper function for hce objects

Description

Helper function for hce objects

Usage

```
hce(  
  GROUP = character(),  
  TRTP = character(),  
  AVAL0 = 0,  
  ORD = sort(unique(GROUP))  
)
```

Arguments

GROUP	a character vector of the same length as AVAL containing events.
TRTP	a character vector of the same length as AVAL containing assigned treatment groups.
AVAL0	a numeric vector of analysis values within each category. The default is 0.
ORD	a character vector containing ordered unique values of the GROUP variable for determining the hierarchy of events.

Value

an object of class hce. Its is a subject-level data frame (each row corresponds to one subject), containing the following columns:

- SUBJID subject ID.
- GROUP a character vector specifying the type of the outcome the patient experienced - either a TTE (time-to-event) or C (continuous).
- GROUPLN a numeric vector version of the GROUP column.
- AVAL0 original analysis values - time of the time-to-event outcomes or the continuous outcome.
- AVAL derived analysis value $AVAL = AVAL0 + GROUPLN$.
- TRTP assigned treatment groups.

See Also

[as_hce\(\)](#) for coercing to hce objects.

Examples

```
# Example 1
set.seed(2022)
d <- hce(GROUP = sample(x = c("A", "B", "C"), size = 10, replace = TRUE),
TRTP = rep(c("Active", "Control"), each = 5),
AVAL0 = c(rnorm(5, mean = 1), rnorm(5)), ORD = c("A", "B", "C"))
calcW0(d, ref = "Control")
```

HCE1	HCE1, HCE2, HCE3, HCE4 <i>datasets for 1000 patients with different treatment effects.</i>
------	--

Description

A simulated dataset containing the ordinal values and other attributes for 1000 patients. HCE1

Usage

HCE1

Format

a data frame with 1000 rows and 6 variables:

ID subject ID, numbers from 1 to 1000

TRTP treatment values, A Active or P Placebo, character

GROUP type of the event, either Time-To-Event (TTE) or Continuous (C), character

GROUPN type of the event, for the ordering of outcomes in the GROUP variable, numeric

AVALT the timing of the time-to-event outcomes, numeric

AVAL0 original values for each type of the event, time for TTE outcomes, numeric values for Continuous outcomes, numeric

AVAL $AVAL = AVAL0 + GROUPN$, ordinal analysis values for the HCE analysis. For the continuous outcome the values of AVAL0 are shifted to start always from 0. Numeric, but caution NOT to apply numeric operations; will give meaningless results

PADY primary analysis day, the length of fixed follow-up in days, numeric

HCE2	HCE1, HCE2, HCE3, HCE4 <i>datasets for 1000 patients with different treatment effects.</i>
------	--

Description

A simulated dataset containing the ordinal values and other attributes for 1000 patients. HCE2

Usage

HCE2

Format

a data frame with 1000 rows and 6 variables:

ID subject ID, numbers from 1 to 1000

TRTP treatment values, A Active or P Placebo, character

GROUP type of the event, either Time-To-Event (TTE) or Continuous (C), character

GROUPN type of the event, for the ordering of outcomes in the GROUP variable, numeric

AVALT the timing of the time-to-event outcomes, numeric

AVAL0 original values for each type of the event, time for TTE outcomes, numeric values for Continuous outcomes, numeric

AVAL $AVAL = AVAL0 + GROUPN$, ordinal analysis values for the HCE analysis. For the continuous outcome the values of AVAL0 are shifted to start always from 0. Numeric, but caution NOT to apply numeric operations; will give meaningless results

PADY primary analysis day, the length of fixed follow-up in days, numeric

HCE3	HCE1, HCE2, HCE3, HCE4 <i>datasets for 1000 patients with different treatment effects.</i>
------	--

Description

A simulated dataset containing the ordinal values and other attributes for 1000 patients. HCE3

Usage

HCE3

Format

a data frame with 1000 rows and 6 variables:

ID subject ID, numbers from 1 to 1000

TRTP treatment values, A Active or P Placebo, character

GROUP type of the event, either Time-To-Event (TTE) or Continuous (C), character

GROUPN type of the event, for the ordering of outcomes in the GROUP variable, numeric

AVALT the timing of the time-to-event outcomes, numeric

AVAL0 original values for each type of the event, time for TTE outcomes, numeric values for Continuous outcomes, numeric

AVAL $AVAL = AVAL0 + GROUPN$, ordinal analysis values for the HCE analysis. For the continuous outcome the values of AVAL0 are shifted to start always from 0. Numeric, but caution NOT to apply numeric operations; will give meaningless results

PADY primary analysis day, the length of fixed follow-up in days, numeric

HCE4	HCE1, HCE2, HCE3, HCE4 <i>datasets for 1000 patients with different treatment effects.</i>
------	--

Description

A simulated dataset containing the ordinal values and other attributes for 1000 patients. HCE4

Usage

HCE4

Format

a data frame with 1000 rows and 6 variables:

ID subject ID, numbers from 1 to 1000

TRTP treatment values, A Active or P Placebo, character

GROUP type of the event, either Time-To-Event (TTE) or Continuous (C), character

GROUPN type of the event, for the ordering of outcomes in the GROUP variable, numeric

AVALT the timing of the time-to-event outcomes, numeric

AVAL0 original values for each type of the event, time for TTE outcomes, numeric values for Continuous outcomes, numeric

AVAL $AVAL = AVAL0 + GROUPN$, ordinal analysis values for the HCE analysis. For the continuous outcome the values of AVAL0 are shifted to start always from 0. Numeric, but caution NOT to apply numeric operations; will give meaningless results

PADY primary analysis day, the length of fixed follow-up in days, numeric

IWP

*Calculates patient-level individual win proportions***Description**

Calculates patient-level individual win proportions

Usage

```
IWP(data, AVAL, TRTP, ref)
```

Arguments

data	a data frame containing subject-level data.
AVAL	variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
ref	the reference treatment group.

Value

the input data frame with a new column of individual win proportions named using the input AVAL value with `_`.

References

Gasparyan SB et al. "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2 (2021): 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558)

See Also

[calcWO\(\)](#), [calcWO.hce\(\)](#), [calcWO.formula\(\)](#).

Examples

```
KHCE1 <- IWP(data = KHCE, AVAL = "EGFRBL", TRTP = "TRTPN", ref = 2)
WP <- tapply(KHCE1$EGFRBL_, KHCE1$TRTPN, mean)
VAR <- tapply(KHCE1$EGFRBL_, KHCE1$TRTPN, function(x) (length(x)-1)*var(x)/length(x))
N <- tapply(KHCE1$EGFRBL_, KHCE1$TRTPN, length)
SE <- sqrt(sum(VAR/N))
c(WP = WP[[1]], SE = SE)
calcWO(EGFRBL ~ TRTP, data = KHCE)[c("WP", "SE_WP")]
```

KHCE

*Kidney Hierarchical Composite Endpoint dataset.***Description**

A dataset with kidney ordinal scale outcomes of 1500 patients in the ADSL dataset.

Usage

KHCE

Format

a data frame with 1500 rows and 11 variables:

ID patient identifiers, numeric

TRTPN treatment values, 1 Active or 2 Placebo, numeric

AVAL0 original values for each type of the event, time for TTE outcomes 1-6, numeric values for Continuous outcome 7, numeric

AVAL $AVAL = AVAL0 + GROUPN$, ordinal analysis values for the HCE analysis, numeric, but caution NOT to apply numeric operations; will give meaningless results

GROUP name of the event, character

GROUPN ordinal outcomes corresponding to PARAMN values, numeric

PARAMCD coded name of the event, character

PARAMN severity of the event, outcomes 1-7, where a higher value means a better outcome, character

STRATAN strata 1-4, higher value means more severe kidney disease, numeric

EGFRBL Baseline GFR values of patients, numeric

TRTP treatment values, A Active or P Placebo, character

PADY primary analysis day (in years), length of the fixed follow-up, numeric

Source

Heerspink HL et al "Development and validation of a new hierarchical composite endpoint for clinical trials of kidney disease progression." *Journal of the American Society of Nephrology* (2023): [doi:10.1681/ASN.000000000000243](https://doi.org/10.1681/ASN.000000000000243).

Examples

```
# Adjusted win odds
res <- regWO(x = KHCE, AVAL = "AVAL", TRTP = "TRTP", COVAR = "STRATAN", ref = "P")
res
```

minWO	<i>Minimum detectable or WO for alternative hypothesis for given power (no ties)</i>
-------	--

Description

Minimum detectable or WO for alternative hypothesis for given power (no ties)

Usage

```
minWO(N, power = 0.5, SD = NULL, k = 0.5, alpha = 0.05, WOnull = 1, digits = 2)
```

Arguments

N	a numeric vector of sample size values (two arms combined).
power	the given power. The default is 0.5 corresponding to the minimum detectable win odds. A numeric vector of length 1.
SD	assumed standard deviation of the win proportion. By default uses the conservative SD. A numeric vector of length 1.
k	proportion of active group in the overall sample size. Default is 0.5 (balanced randomization). A numeric vector of length 1.
alpha	the significance level for the 2-sided test. Default is 0.05. A numeric vector of length 1.
WOnull	the win odds value of the null hypothesis (default is 1). A numeric vector of length 1.
digits	precision to use for reporting calculated win odds.

Value

a data frame containing the calculated WO with input values.

References

Gasparian SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. [doi:10.1080/10543406.2021.1968893](https://doi.org/10.1080/10543406.2021.1968893)

See Also

[powerWO\(\)](#), [sizeWO\(\)](#) for WO power and sample size calculation.

Examples

```

minWO(N = 100, digits = 5)
minWO(N = 1200, power = 0.9, k = 0.75)
# Compare the minimum detectable win odds from shifted alternatives to max and ordered alternatives
WO <- minWO(N = 1200, k = 0.5, power = 0.67, digits = 7)$WO
powerWO(N = 1200, WO = WO, k = 0.5, alternative = "shift")
powerWO(N = 1200, WO = WO, k = 0.5, alternative = "ordered")
powerWO(N = 1200, WO = WO, k = 0.5, alternative = "max")

```

plot.hce

*A plot method for hce objects***Description**

Ordinal dominance graph for hce objects

Usage

```

## S3 method for class 'hce'
plot(x, fill = FALSE, ...)

```

Arguments

x	an object of class hce created by as_hce().
fill	logical; if TRUE fill the area above the graph.
...	additional arguments to be passed to <code>base::plot()</code> function.

Value

no return value, called for plotting.

References

Bamber D. "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4 (1975): 387-415. doi:[10.1016/0022-2496\(75\)90001-2](https://doi.org/10.1016/0022-2496(75)90001-2)

Examples

```

d <- as_hce(KHCE)
d$TRTP <- factor(d$TRTP, levels = c("P", "A"))
res <- calcWO(AVAL ~ TRTP, data = d)
# Ordinal Dominance Graph
plot(d, col = 3, type = 'l')
grid()
# Area above the Ordinal Dominance Graph
plot(d, fill = TRUE, col = "#865A4F", type = 'l',
      lwd = 2, xlab = "Control", ylab = "Active")
legend("bottomright", legend = paste0("WP = ", round(res$WP, 5)))
abline(a = 0, b = 1, lwd = 2, lty = 2, col = "#999999")

```

plot.hce_results *A print method for hce_results objects*

Description

A print method for hce_results objects

Usage

```
## S3 method for class 'hce_results'
plot(x, ...)
```

Arguments

x an object of class hce_results.
 ... additional arguments to be passed to `base::plot()` function.

Value

no return value, called for plotting.

Examples

```
WO <- minWO(N = 100:1000)
plot(WO)
POW <- powerWO(N = 100:1000, WO = 1.2)
plot(POW, ylim = c(0, 1))
```

powerWO *Power calculation for the win odds test (no ties)*

Description

Power calculation for the win odds test (no ties)

Usage

```
powerWO(
  N,
  WO,
  SD = NULL,
  k = 0.5,
  alpha = 0.05,
  WOnull = 1,
  alternative = c("shift", "max", "ordered")
)
```

Arguments

N	a numeric vector of sample size values.
WO	the given win odds for the alternative hypothesis. A numeric vector of length 1.
SD	assumed standard deviation of the win proportion. By default uses the conservative SD. A numeric vector of length 1.
k	proportion of active group in the overall sample size. Default is 0.5 (balanced randomization). A numeric vector of length 1.
alpha	the significance level for the 2-sided test. Default is 0.05. A numeric vector of length 1.
WOnull	the win odds value of the null hypothesis (default is 1). A numeric vector of length 1.
alternative	a character string specifying the class of the alternative hypothesis, must be one of "shift" (default), "max" or "ordered". You can specify just the initial letter.

Details

alternative = "max" refers to the maximum variance of the win proportion across all possible alternatives. The maximum variance equals $WP \cdot (1 - WP) / k$ where the win probability is calculated as $WP = WO / (WO + 1)$. alternative = "shift" specifies the variance across alternatives from a shifted family of distributions (Wilcoxon test). The variance formula, as suggested by Noether, is calculated based on the null hypothesis as follows $1 / (12 \cdot k \cdot (1 - k))$. alternative = "ordered" specifies the variance across alternatives from stochastically ordered distributions which include shifted distributions.

Value

a data frame containing the calculated power with input values.

References

- All formulas were presented in

Bamber D (1975) "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4: 387-415. doi:10.1016/0022-2496(75)90001-2.

- Noether's formula for shifted alternatives

Noether GE (1987) "Sample size determination for some common nonparametric tests." *Journal of the American Statistical Association* 82.398: 645-7. doi:10.1080/01621459.1987.10478478.

- For shift alternatives see also

Gasparyan SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. doi:10.1080/10543406.2021.1968893.

See Also

`sizeWO()`, `minWO()` for WO sample size or minimum detectable WO calculation.

Examples

```
# Example 1- Use the default standard deviation
powerWO(N = 1000, WO = 1.2)
powerWO(N = seq(500, 1500, 100), WO = 1.2)
# Example 2 - Use data-driven win odds and standard deviation from the COVID19 dataset
res <- calcWO(x = COVID19, AVAL = "GROUP", TRTP = "TRTP", ref = "Placebo")
print(res)
powerWO(N = 500, WO = res$WO, SD = res$SD_WP)
powerWO(N = 500, WO = res$WO) # power with the default standard deviation for the win proportion.
# Example 3 - Non-balanced 3:1 randomization
powerWO(N = 1000, WO = 1.2, k = 0.75)
# Example 4 - Comparison of different alternatives
powerWO(N = 1000, WO = 1.2, alternative = "m")
powerWO(N = 1000, WO = 1.2, alternative = "s")
powerWO(N = 1000, WO = 1.2, alternative = "o")
```

print.hce_results *A print method for hce_results objects*

Description

A print method for hce_results objects

Usage

```
## S3 method for class 'hce_results'
print(x, ...)
```

Arguments

`x` an object of class hce_results.
`...` additional arguments to be passed to `base::print()` function.

Value

no return value, called for printing.

Examples

```
print(powerWO(N = 1000, WO = 1.2))
```

propWINS	<i>Proportion of wins/losses/ties given the win odds and the win ratio</i>
----------	--

Description

Proportion of wins/losses/ties given the win odds and the win ratio

Usage

```
propWINS(WO, WR, Overall = 1, alpha = NULL, N = NULL)
```

Arguments

WO	win odds.
WR	win ratio.
Overall	number of comparisons, the sample size of the active treatment multiplied by the sample size of the placebo. The default is 1, hence gives the proportion.
alpha	significance level for the win ratio confidence interval. The default is NULL hence the confidence interval is not produced.
N	the combined sample size of two treatment groups. The default is NULL. If alpha is specified then either N should be specified or Overall > 1. For given Overall, the pooled sample size is calculated as $N = 2 * \text{sqrt}(\text{Overall})$.

Details

- **Win ratio** defined as $WR = \frac{W}{L}$.
- **Win odds** defined as $WO = \frac{W+0.5T}{L+0.5T} = \frac{WP}{1-WP}$.
- **Net Benefit** defined as $NB = \frac{W-L}{O}$.

Given the overall number of comparisons O , the win proportion WP and the win ratio WR , it is possible to find the total number of wins and losses. Indeed, first the win odds can be found $WO = \frac{WP}{1-WP}$ and

$$L = O * \frac{2WP - 1}{WR - 1},$$

$$W = WR * O * \frac{2WP - 1}{WR - 1},$$

$$T = O - W - L.$$

Value

a data frame with a number (or proportion if Overall = 1) of wins/losses/ties. If alpha is specified returns also WR confidence interval.

References

- For the relationship between win odds and win ratio see
 Gasparian SB et al. "Hierarchical Composite Endpoints in COVID-19: The DARE-19 Trial".
 Case Studies in Innovative Clinical Trials, Chapter 7 (2023): 95-148. Chapman and Hall/CRC.
[doi:10.1201/9781003288640-7](https://doi.org/10.1201/9781003288640-7).
- The win ratio CI uses the standard error presented in
 Yu RX, Ganju J. (2022) "Sample size formula for a win ratio endpoint." Statistics in Medicine
 41.6: 950-63. [doi:10.1002/sim.9297](https://doi.org/10.1002/sim.9297).

Examples

```
# Example 1
propWINS(WR = 2, WO = 1.5)
# Example 2 - Back-calculation
COVID19HCE <- hce(GROUP = COVID19$GROUP, TRTP = COVID19$TRTP)
res <- calcWINS(COVID19HCE)
WR <- res$WR1$WR
WO <- res$WO$WO
Overall <- res$summary$TOTAL
propWINS(WR = WR, WO = WO, Overall = Overall)
## Verify
res$summary
# Example 3 - Confidence interval
propWINS(WR = 1.4, WO = 1.3, alpha = 0.05, Overall = 2500)
propWINS(WR = 2, WO = 1.5, alpha = 0.01, N = 500)
```

regWO

A generic function for win odds regression

Description

A generic function for win odds regression

Usage

```
regWO(x, ...)
```

Arguments

x an object used to select a method.
 ... further arguments passed to or from other methods.

Value

a data frame containing calculated values.

See Also

[regWO.data.frame\(\)](#), [regWO.formula\(\)](#) methods.

regWO.data.frame *Win Odds Regression Using a Data Frame*

Description

This function performs regression analysis for the win odds using a single numeric covariate.

Usage

```
## S3 method for class 'data.frame'  
regWO(x, AVAL, TRTP, COVAR, ref, alpha = 0.05, WOnull = 1, ...)
```

Arguments

x	a data frame containing subject-level data.
AVAL	a variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
COVAR	a numeric covariate.
ref	the reference treatment group.
alpha	the significance level, with a default value of 0.05.
WOnull	the null hypothesis value for win odds. The default is 1.
...	additional parameters.

Value

a data frame containing the calculated win odds and its confidence interval, including:

- WO_beta adjusted win odds.
- LCL lower confidence limit for adjusted WO.
- UCL upper confidence limit for adjusted WO.
- SE standard error of the adjusted win odds.
- WOnull win odds of the null hypothesis (specified in the WOnull argument).
- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- N total number of patients in the analysis.
- beta adjusted win probability.
- LCL_beta lower confidence limit for adjusted win probability.
- UCL_beta upper confidence limit for adjusted win probability.

- SE_beta standard error for the adjusted win probability.
- SD_beta standard deviation for the adjusted win probability.
- WP (non-adjusted) win probability.
- SE_WP standard error of the non-adjusted win probability.
- SD_WP standard deviation of the non-adjusted win probability.
- WO non-adjusted win odds.
- COVAR_MEAN_DIFF mean difference between two treatment groups of the numeric covariate.
- COVAR_VAR sum of variances of two treatment groups of the numeric covariate.
- COVAR_COV covariance between the response and the numeric covariate.

References

Gasparyan SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558).

See Also

[regWO\(\)](#), [regWO.formula\(\)](#).

Examples

```
# A baseline covariate that is highly correlated with the outcome
set.seed(2023)
dat <- COVID19
n <- nrow(dat)
dat$Severity <- ifelse(dat$GROUP > 4, rnorm(n, 0), rnorm(n, 100))
tapply(dat$Severity, dat$TRTP, mean)
regWO(x = dat, AVAL = "GROUP", TRTP = "TRTP", COVAR = "Severity", ref = "Placebo")
# Without adjustment
calcWO(x = dat, AVAL = "GROUP", TRTP = "TRTP", ref = "Placebo")
```

regWO.formula

Win Odds Regression Using a Formula Syntax

Description

This function performs regression analysis for the win odds using a single numeric covariate.

Usage

```
## S3 method for class 'formula'
regWO(x, data, ...)
```

Arguments

x	an object of class formula.
data	a data frame.
...	additional parameters.

Value

a data frame containing the calculated win odds and its confidence interval, including:

- WO_beta adjusted win odds.
- LCL lower confidence limit for adjusted WO.
- UCL upper confidence limit for adjusted WO.
- SE standard error of the adjusted win odds.
- WOnull win odds of the null hypothesis (specified in the WOnull argument).
- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- N total number of patients in the analysis.
- beta adjusted win probability.
- LCL_beta lower confidence limit for adjusted win probability.
- UCL_beta upper confidence limit for adjusted win probability.
- SE_beta standard error for the adjusted win probability.
- SD_beta standard deviation for the adjusted win probability.
- WP (non-adjusted) win probability.
- SE_WP standard error of the non-adjusted win probability.
- SD_WP standard deviation of the non-adjusted win probability.
- WO non-adjusted win odds.
- COVAR_MEAN_DIFF mean difference between two treatment groups of the numeric covariate.
- COVAR_VAR sum of variances of two treatment groups of the numeric covariate.
- COVAR_COV covariance between the response and the numeric covariate.
- formula returning the specified formula in the x argument.
- ref showing how the reference group was selected. Can be modifying by specifying the ref argument.

References

Gasparyan SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558).

See Also

[regWO\(\)](#), [regWO.data.frame\(\)](#).

Examples

```
regWO(AVAL ~ TRTP, data = KHCE)
regWO(AVAL ~ TRTP + EGFRBL, data = KHCE)
```

simHCE	<i>Simulate hce object with given event rates of time-to-event outcomes (Weibull), mean and SD of the continuous outcome (normal or log-normal) by treatment group</i>
--------	--

Description

Simulate hce object with given event rates of time-to-event outcomes (Weibull), mean and SD of the continuous outcome (normal or log-normal) by treatment group

Usage

```
simHCE(
  n,
  n0 = n,
  TTE_A,
  TTE_P,
  CM_A,
  CM_P,
  CSD_A = 1,
  CSD_P = CSD_A,
  fixedfy = 1,
  yeardays = 360,
  pat = 100,
  shape = 1,
  theta = 1,
  logC = FALSE,
  seed = NULL,
  dec = 2,
  all_data = FALSE
)
```

Arguments

n	sample size in the active treatment group.
n0	sample size in the placebo group.
TTE_A	event rates per year in the active group for the time-to-event outcomes.
TTE_P	event rates per year in the placebo group for the time-to-event outcomes. Should have the same length as TTE_A.
CM_A	mean value for the continuous outcome of the active group.
CM_P	mean value for the continuous outcome of the placebo group.

CSD_A	standard deviation for the continuous outcome of the active group.
CSD_P	standard deviation for the continuous outcome of the placebo group.
fixedfy	length of follow-up in years.
yeardays	number of days in a year.
pat	scale of provided event rates (per pat-years).
shape	shape of the Weibull distribution for time-to-event outcomes. Default is exponential distribution with shape = 1.
theta	Gumbel dependence coefficient of the Weibull distributions for time-to-event outcomes. Default is theta = 1 which assumes independence of time-to-event outcomes. Must be above or equal to 1.
logC	logical, whether to use log-normal distribution for the continuous outcome.
seed	for generating random numbers.
dec	decimal places for the continuous outcome used for rounding. The default is dec = 2.
all_data	logical, whether to return source datasets ADET (an event-time dataset for all time-to-event outcomes per patient) and BDS (a basic data structure for the continuous outcome for all patients).

Value

an object of class `hce` containing the following columns:

- ID subject identifier.
- TRTP planned treatment group - "A" for active, "P" for Placebo.
- GROUP type of the outcome, either "TTE" for time-to-event outcomes or "C" for continuous. Only one continuous outcome is possible, but no restriction on the number of "TTE" outcomes.
- GROUPN order of outcomes in GROUP, with a higher value signifying a better outcome.
- AVALT the timing of the time-to-event outcomes.
- AVAL0 numeric values of the continuous outcome and the timing of "TTE" outcomes.
- AVAL analysis values derived as $AVAL0 + GROUPN$. For the continuous outcome the values of AVAL0 are shifted to start always from 0.
- seed the seed of the random sample. If not specified in seed argument will be selected based on system time.
- PADY primary analysis day, the length of fixed follow-up in days calculated as `yeardays` multiplied by `fixedfy`.

If `all_data = TRUE`, the function returns a list containing the `hce` dataset, along with its source datasets: ADET (an event-time dataset for all time-to-event outcomes per patient) and BDS (a basic data structure for the continuous outcome for all patients).

See Also

[hce\(\)](#), [as_hce\(\)](#) for the helper a coerce function to `hce` objects.

Examples

```
# Example 1
Rates_A <- c(1.72, 1.74, 0.58, 1.5, 1)
Rates_P <- c(2.47, 2.24, 2.9, 4, 6)
dat <- simHCE(n = 2500, TTE_A = Rates_A, TTE_P = Rates_P,
             CM_A = -3, CM_P = -6, CSD_A = 16, CSD_P = 15, fixedfy = 3)
head(dat)

# Example 2
Rates_A <- 10
Rates_P <- 15
dat <- simHCE(n = 1000, n0 = 500, TTE_A = Rates_A, TTE_P = Rates_P,
             CM_A = 0.1, CM_P = 0, seed = 5, shape = 0.2, logC = TRUE, dec = 0)
summaryWO(dat)

# Example 3: Comparison of dependent and independent outcomes
Rates_A <- c(10, 20)
Rates_P <- c(20, 20)
dat1 <- simHCE(n = 2500, TTE_A = Rates_A, TTE_P = Rates_P,
             CM_A = -3, CM_P = -6, CSD_A = 15, fixedfy = 3, theta = 1, seed = 1)
dat2 <- simHCE(n = 2500, TTE_A = Rates_A, TTE_P = Rates_P,
             CM_A = -3, CM_P = -6, CSD_A = 15, fixedfy = 3, theta = 1.0001, seed = 1)
calcWO(dat1)
calcWO(dat2)
```

 simKHCE

Simulate a kidney disease hce dataset

Description

Simulate a kidney disease hce dataset, capturing eGFR (Estimated Glomerular Filtration Rate) progression over time, along with a competing and dependent terminal event: KFRT (Kidney Failure Replacement Therapy)

Usage

```
simKHCE(
  n,
  CM_A,
  CM_P = -4,
  n0 = n,
  TTE_A = 10,
  TTE_P = TTE_A,
  fixedfy = 2,
  Emin = 20,
  Emax = 100,
  sigma = 8,
  Sigma = 3,
```

```

    m = 10,
    theta = -0.23,
    phi = 0
  )

```

Arguments

n	sample size in the active treatment group.
CM_A	annualized eGFR slope in the active group.
CM_P	annualized eGFR slope in the control group.
n0	sample size in the control treatment group.
TTE_A	event rate per year in the active group for KFRT.
TTE_P	event rate per year in the placebo group for KFRT.
fixedfy	length of follow-up in years.
Emin	lower limit of eGFR at baseline.
Emax	upper limit of eGFR at baseline.
sigma	within-patient standard deviation.
Sigma	between-patient standard deviation.
m	number of equidistant visits.
theta	coefficient of dependence of eGFR values and the risk of KFRT.
phi	coefficient of proportionality (between 0 and 1) of the treatment effect. The case of 0 corresponds to the uniform treatment effect.

Value

a list containing the dataset GFR for longitudinal measurements of eGFR and the competing KFRT events, the dataset ADET for the time-to-event kidney outcomes (sustained declines or sustained low levels of eGFR), and the combined HCE dataset for the kidney hierarchical composite endpoint.

See Also

[simHCE\(\)](#) for a general function of simulating hce datasets.

Examples

```

# Example 1
set.seed(2022)
L <- simKHCE(n = 1000, CM_A = -3.25)
dat <- L$HCE
calcWO(dat)

```

simORD	<i>Simulate ordinal variables for two treatment groups using categorization of beta distributions</i>
--------	---

Description

Simulate ordinal variables for two treatment groups using categorization of beta distributions

Usage

```
simORD(n, n0 = n, M, alpha1 = 8, beta1 = 7, alpha0 = 5, beta0 = 5)
```

Arguments

n	sample size in the active treatment group.
n0	sample size in the placebo group.
M	number of ordinal values to be simulated.
alpha1	shape1 parameter for the beta distribution in the active group.
beta1	shape2 parameter for the beta distribution in the active group.
alpha0	shape1 parameter for the beta distribution in the placebo group.
beta0	shape2 parameter for the beta distribution in the placebo group.

Value

a data frame containing the following columns:

- ID subject identifier.
- TRTP planned treatment group - "A" for active, "P" for Placebo.
- GROUPN ordinal values. The number of unique values is specified by the variable M0.
- tau the theoretical win odds.
- theta the theoretical win probability.

See Also

[simHCE\(\)](#) for simulating hce objects.

Examples

```
# Example 1
set.seed(2024)
alpha1 <- 8
beta1 <- 8
alpha0 <- 4
beta0 <- 5
d <- simORD(n = 1500, n0 = 1500, M = 5, alpha1 = alpha1, beta1 = beta1,
```

```

alpha0 = alpha0, beta0 = beta0)
x <- seq(0, 1, 0.01)
plot(x, dbeta(x, shape1 = alpha1, shape2 = beta1),
type = "l", ylab = "Density of beta distribution", col = 2)
lines(x, dbeta(x, shape1 = alpha0, shape2 = beta0), col = 3, lty = 2)
legend("topleft", lty = c(1, 2), col = c(2, 3), legend = c("Control", "Active"))
D <- hce(GROUP = d$GROUPN, TRTP = d$TRTP)
table(D$TRTP, D$GROUPN)
calcWO(D)
# Example 2
set.seed(2024)
d <- simORD(n = 100, n0 = 50, M = 2)
d_hce <- hce(GROUP = d$GROUPN, TRTP = d$TRTP)
calcWO(d_hce)
### compare with the theoretical values of the continuous distributions
c(tau = unique(d$tau), theta = unique(d$theta))
# Example 2 - Convergence of the win odds to its theoretical value
set.seed(2024)
N <- NULL
size <- c(seq(10, 500, 1))
for(i in size){
  d <- simORD(n = i, M = 2)
  d_hce <- hce(GROUP = d$GROUPN, TRTP = d$TRTP)
  TAU <- calcWO(d_hce)
  D <- data.frame(WO = TAU$WO, n = i, tau = unique(d$tau))
  N <- rbind(N, D)
}
plot(N$n, N$WO, log = "y", ylim = c(0.5, 2), ylab = "Win Odds", xlab = "Sample size", type = "l")
lines(N$n, N$tau, col = "darkgreen", lty = 2, lwd = 2)
abline(h = 1, lty = 4, col = "red")
legend("bottomright", legend = c("Theoretical Win Odds", "Null", "Win Odds Estimate"),
lty = c(4, 2, 1), col = c("darkgreen", "red", "black"))
title("Convergence of the win odds to its theoretical value")

```

sizeWO

Sample size calculation for the win odds test (no ties)

Description

Sample size calculation for the win odds test (no ties)

Usage

```

sizeWO(
  WO,
  power,
  SD = NULL,
  k = 0.5,
  alpha = 0.05,
  WOnull = 1,

```

```

    alternative = c("shift", "max", "ordered")
  )

```

Arguments

WO	a numeric vector of win odds values.
power	the given power. A numeric vector of length 1.
SD	assumed standard deviation of the win proportion. By default uses the conservative SD. A numeric vector of length 1.
k	proportion of active group in the overall sample size. Default is 0.5 (balanced randomization). A numeric vector of length 1.
alpha	the significance level for the 2-sided test. Default is 0.05. A numeric vector of length 1.
WOnull	the win odds value of the null hypothesis (default is 1). A numeric vector of length 1.
alternative	a character string specifying the class of the alternative hypothesis, must be one of "shift" (default), "max" or "ordered". You can specify just the initial letter.

Details

alternative = "max" refers to the maximum variance of the win proportion across all possible alternatives. The maximum variance equals $WP \cdot (1 - WP) / k$ where the win probability is calculated as $WP = WO / (WO + 1)$. alternative = "shift" specifies the variance across alternatives from a shifted family of distributions (Wilcoxon test). The variance formula, as suggested by Noether, is calculated based on the null hypothesis as follows $1 / (12 \cdot k \cdot (1 - k))$. alternative = "ordered" specifies the variance across alternatives from stochastically ordered distributions which include shifted distributions.

Value

a data frame containing the sample size with input values.

References

- All formulas were presented in
 - Bamber D (1975) "The area above the ordinal dominance graph and the area below the receiver operating characteristic graph." *Journal of Mathematical Psychology* 12.4: 387-415. doi:10.1016/0022-2496(75)90001-2.
- Noether's formula for shifted alternatives
 - Noether GE (1987) "Sample size determination for some common nonparametric tests." *Journal of the American Statistical Association* 82.398: 645-7. doi:10.1080/01621459.1987.10478478.
- For shift alternatives see also

Gasparyan SB et al. (2021) "Power and sample size calculation for the win odds test: application to an ordinal endpoint in COVID-19 trials." *Journal of Biopharmaceutical Statistics* 31.6: 765-787. doi:10.1080/10543406.2021.1968893.

See Also

`powerWO()`, `minWO()` for WO power or minimum detectable WO calculation.

Examples

```
sizeWO(WO = 1.25, power = 0.9)
sizeWO(WO = 1.25, power = 0.9, k = 0.75)
sizeWO(WO = seq(1.05, 1.5, 0.05), power = 0.9)
# Comparison of different alternatives
x <- seq(1.05, 5, 0.05)
N1 <- sizeWO(WO = x, power = 0.9, alternative = "m")$SampleSize
N2 <- sizeWO(WO = x, power = 0.9, alternative = "o")$SampleSize
N3 <- sizeWO(WO = x, power = 0.9, alternative = "s")$SampleSize
d <- data.frame(WO = x, N_m = N1, N_o = N2, N_s = N3)
## Check the power for the ordered alternative
check <- c()
for(i in seq_along(x)){
  check[i] <- powerWO(N = d[i, "N_o"], WO = d[i, "WO"], alternative = "o")$power
}
d$power_check_o <- check
print(d)
```

sizeWR	<i>Sample size calculation for the win ratio test (with WR = 1 null hypothesis)</i>
--------	---

Description

Sample size calculation for the win ratio test (with WR = 1 null hypothesis)

Usage

```
sizeWR(WR, power, WO = NULL, Pties = NULL, k = 0.5, alpha = 0.05)
```

Arguments

WR	a numeric vector of win odds values.
power	the given power. A numeric vector of length 1.
WO	win odds. Should be specified only if Pties is not specified. A numeric vector of length 1.
Pties	probability of ties. A numeric vector of length 1.
k	proportion of active group in the overall sample size. Default is 0.5 (balanced randomization). A numeric vector of length 1.
alpha	the significance level for the 2-sided test. Default is 0.05. A numeric vector of length 1.

Value

a data frame containing the sample size with input values.

References

Yu RX, Ganju J. (2022) "Sample size formula for a win ratio endpoint." *Statistics in Medicine*, 41.6: 950-63. doi:10.1002/sim.9297.

See Also

[sizeWO\(\)](#) for WO sample size calculation.

Examples

```
sizeWR(WR = 1.35, Pties = 0.125, power = 0.8)
sizeWR(WR = 1.35, WO = 1.3, power = seq(0.5, 0.9, 0.05))
```

stratWO

A generic function for stratified win odds with adjustment

Description

A generic function for stratified win odds with adjustment

Usage

```
stratWO(x, ...)
```

Arguments

x an object used to select a method.
... further arguments passed to or from other methods.

Value

a list containing the stratified results and results by strata.

See Also

[stratWO.data.frame\(\)](#) methods.

stratWO.data.frame *Stratified win odds with adjustment*

Description

Stratified win odds with adjustment

Usage

```
## S3 method for class 'data.frame'
stratWO(
  x,
  AVAL,
  TRTP,
  STRATA,
  ref,
  COVAR = NULL,
  alpha = 0.05,
  WOnull = 1,
  ...
)
```

Arguments

x	a data frame containing subject-level data.
AVAL	variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
STRATA	a character variable for stratification.
ref	the reference treatment group.
COVAR	a numeric covariate.
alpha	the reference treatment group.
WOnull	the null hypothesis. The default is 1.
...	additional parameters.

Value

a data frame containing the following columns:

- WO stratified (or adjusted/stratified) win odds.
- LCL lower confidence limit for adjusted (or adjusted/stratified) WO.
- UCL upper confidence limit for adjusted (or adjusted/stratified) WO.
- SE standard error of the adjusted (or adjusted/stratified) win odds.
- WOnull win odds of the null hypothesis (specified in the WOnull argument).

- alpha two-sided significance level for calculating the confidence interval (specified in the alpha argument).
- Pvalue p-value associated with testing the null hypothesis.
- WP adjusted (or adjusted/stratified) win probability.
- LCL_WP lower confidence limit for adjusted (or adjusted/stratified) WP.
- UCL_WP upper confidence limit for adjusted (or adjusted/stratified) WP.
- SE_WP standard error for the adjusted (or adjusted/stratified) win probability.
- SD_WP standard deviation of the adjusted (or adjusted/stratified) win probability.
- N total number of patients in the analysis.
- Type "STRATIFIED" or "STRATIFIED/ADJUSTED" depending on whether COVAR is specified.

References

Gasparyan SB et al. (2021) "Adjusted win ratio with stratification: calculation methods and interpretation." *Statistical Methods in Medical Research* 30.2: 580-611. doi:[10.1177/0962280220942558](https://doi.org/10.1177/0962280220942558).

See Also

[stratWO\(\)](#).

Examples

```
# Stratified win odds
res <- stratWO(x = KHCE, AVAL = "AVAL", TRTP = "TRTP",
              STRATA = "STRATAN", ref = "P")

res
## Compare with the non-stratified win odds
res0 <- calcWO(AVAL ~ TRTP, data = KHCE, ref = "P")
res0
## Compare with the win odds in each stratum separately
l <- lapply(split(KHCE, KHCE$STRATAN), calcWO, AVAL = "AVAL", TRTP = "TRTP", ref = "P")
l <- do.call(rbind, l)
l <- l[, c("WO", "LCL", "UCL", "N")]
l$STRATA <- as.numeric(row.names(l))
plot(y = l$WO, x = l$STRATA, ylim = c(0.5, 2.5), log = "y", xlim = c(0, 6),
     ylab = "Win Odds", xlab = "", xaxt = "n")
axis(1, at = 1:6, labels = c(paste0("STR = ", l$STRATA), "Stratified", "Non-stratified"))
arrows(l$STRATA, l$LCL, l$STRATA,
       l$UCL, angle = 90, code = 3, length = 0.05, col = "darkgreen")
points(5, res$WO)
arrows(5, res$LCL, 5, res$UCL, angle = 90, code = 3,
      length = 0.05, col = "darkblue")
abline(h = c(1, res$WO), col = "red", lty = 4)
points(6, res0$WO)
arrows(6, res0$LCL, 6, res0$UCL, angle = 90, code = 3,
      length = 0.05, col = "darkred")
# Stratified and adjusted win odds
res <- stratWO(x = KHCE, AVAL = "AVAL", COVAR = "EGFRBL",
```

```

      TRTP = "TRTP", STRATA = "STRATAN", ref = "P")
res

```

summaryWO	<i>A generic function for summarizing win odds</i>
-----------	--

Description

A generic function for summarizing win odds

Usage

```
summaryWO(x, ...)
```

Arguments

x	an object used to select a method.
...	further arguments passed to or from other methods.

Value

a data frame containing calculated values.

See Also

[summaryWO.hce\(\)](#), [summaryWO.formula\(\)](#), [summaryWO.data.frame\(\)](#) methods.

summaryWO.data.frame	<i>Win odds summary for a data frame</i>
----------------------	--

Description

Win odds summary for a data frame

Usage

```

## S3 method for class 'data.frame'
summaryWO(x, AVAL, TRTP, ref, GROUP = NULL, ...)

```

Arguments

x	a data frame containing subject-level data.
AVAL	variable in the data with ordinal analysis values.
TRTP	the treatment variable in the data.
ref	the reference treatment group.
GROUP	an optional variable for grouping.
...	additional parameters.

Value

a list containing the summary of wins, losses, and ties. It contains the following named objects:

- summary a data frame containing number of wins, losses, and ties by treatment group and the overall number of comparisons.
- summary_by_GROUP (if GROUP variable is specified) a summary data frame by GROUP.
- WO calculated WO (win odds) and WP (win probability) and their standard errors.

See Also

[calcWO\(\)](#), [summaryWO\(\)](#), [summaryWO.formula\(\)](#), [summaryWO.hce\(\)](#) methods.

Examples

```
summaryWO(x = HCE3, AVAL = "AVAL", TRTP = "TRTP", ref = "P", GROUP = "GROUP")
```

summaryWO.formula	<i>Win odds summary using formula syntax</i>
-------------------	--

Description

Win odds summary using formula syntax

Usage

```
## S3 method for class 'formula'
summaryWO(x, data, ...)
```

Arguments

x	an object of class formula.
data	a data frame.
...	additional parameters.

Value

a list containing the summary of wins, losses, and ties. It contains the following named objects:

- summary a data frame containing number of wins, losses, and ties by treatment group and the overall number of comparisons.
- WO calculated WO (win odds) and WP (win probability) and their standard errors.
- formula returning the specified formula in the x argument.
- ref showing how the reference group was selected. Can be modifying by specifying the ref argument.

See Also

[calcWO\(\)](#), [summaryWO\(\)](#), [summaryWO.data.frame\(\)](#), [summaryWO.hce\(\)](#) methods.

Examples

```
summaryWO(data = COVID19, GROUP ~ TRTP)
summaryWO(data = COVID19, GROUP ~ TRTP, GROUP = "GROUP", ref = "Placebo")
```

summaryWO.hce	<i>Win odds summary for hce objects</i>
---------------	---

Description

Win odds summary for hce objects

Usage

```
## S3 method for class 'hce'
summaryWO(x, ...)
```

Arguments

```
x          an hce object.
...        additional parameters.
```

Value

a list containing the summary of wins, losses, and ties. It contains the following named objects:

- summary a data frame containing number of wins, losses, and ties by treatment group and the overall number of comparisons.
- summary_by_GROUP (if GROUP variable is specified) a summary data frame by GROUP.
- WO calculated WO (win odds) and WP (win probability) and their standard errors.

See Also

[calcWO\(\)](#), [summaryWO\(\)](#), [summaryWO.data.frame\(\)](#), [summaryWO.formula\(\)](#) methods.

Examples

```
dat <- as_hce(HCE4)
summaryWO(dat, ref = "P")
```

Index

* datasets

- ADET, 3
 - ADLB, 4
 - ADSL, 5
 - COVID19, 20
 - COVID19b, 20
 - COVID19plus, 21
 - HCE1, 23
 - HCE2, 24
 - HCE3, 24
 - HCE4, 25
 - KHCE, 27
- ADET, 3
- ADLB, 4
- ADSL, 5
- as_hce, 5
- as_hce(), 6, 7, 22, 39
- as_hce.data.frame, 6
- as_hce.data.frame(), 6, 7
- as_hce.default, 7
- as_hce.default(), 6
- base::plot(), 29, 30
- base::print(), 32
- calcWINS, 7
- calcWINS(), 10, 13, 15
- calcWINS.data.frame, 8
- calcWINS.data.frame(), 8, 13, 15
- calcWINS.formula, 11
- calcWINS.formula(), 8, 10, 15
- calcWINS.hce, 13
- calcWINS.hce(), 8, 10, 13
- calcWO, 15
- calcWO(), 17–19, 26, 50, 51
- calcWO.data.frame, 16
- calcWO.data.frame(), 16, 18, 19
- calcWO.formula, 17
- calcWO.formula(), 16, 17, 19, 26
- calcWO.hce, 18
- calcWO.hce(), 16–18, 26
- COVID19, 20
- COVID19b, 20
- COVID19plus, 21
- hce, 22
- hce(), 39
- HCE1, 23
- HCE2, 24
- HCE3, 24
- HCE4, 25
- IWP, 26
- KHCE, 27
- minWO, 28
- minWO(), 32, 45
- plot.hce, 29
- plot.hce_results, 30
- powerWO, 30
- powerWO(), 28, 45
- print.hce_results, 32
- propWINS, 33
- regWO, 34
- regWO(), 36, 37
- regWO.data.frame, 35
- regWO.data.frame(), 35, 37
- regWO.formula, 36
- regWO.formula(), 35, 36
- simHCE, 38
- simHCE(), 41, 42
- simKHCE, 40
- simORD, 42
- sizeWO, 43
- sizeWO(), 28, 32, 46
- sizeWR, 45

stratWO, [46](#)
stratWO(), [48](#)
stratWO.data.frame, [47](#)
stratWO.data.frame(), [46](#)
summaryWO, [49](#)
summaryWO(), [50](#), [51](#)
summaryWO.data.frame, [49](#)
summaryWO.data.frame(), [49](#), [51](#)
summaryWO.formula, [50](#)
summaryWO.formula(), [49–51](#)
summaryWO.hce, [51](#)
summaryWO.hce(), [49–51](#)