

Multipath TCP  
INTERNET-DRAFT  
Intended Status: Standard Track  
Expires: August 18, 2014

Ramin Khalili  
T-Labs/TU-Berlin  
Nicolas Gast  
Miroslav Popovic  
Jean-Yves Le Boudec  
EPFL-LCA2  
February 14, 2014

Opportunistic Linked-Increases Congestion Control Algorithm for MPTCP  
draft-khalili-mptcp-congestion-control-04

Abstract

This document describes the mechanism of OLIA, the "Opportunistic Linked Increases Algorithm". OLIA is a congestion control algorithm for MPTCP. The current congestion control algorithm of MPTCP, LIA [4], forces a tradeoff between optimal congestion balancing and responsiveness. OLIA's design departs from this tradeoff and provide these properties simultaneously. Hence, it solves the identified performance problems with LIA while retaining non-flappiness and responsiveness behavior of LIA, as shown by different studies [5, 6, 7, 8]. OLIA is now part of the UCLouvain's MPTCP implementation [9].

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 18, 2014.

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/lid-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at  
<http://www.ietf.org/shadow.html>

## Copyright and License Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1	Introduction . . . . .	3
1.1	Requirements Language . . . . .	4
1.2	Terminology . . . . .	4
2	The set of best paths, paths with maximum windows, and collected paths . . . . .	5
3	Opportunistic Linked-Increases Algorithm . . . . .	7
4	Practical considerations . . . . .	9
5	Discussion . . . . .	10
6	References . . . . .	11
6.1	Normative References . . . . .	11
6.2	Informative References . . . . .	11
	Authors' Addresses . . . . .	12

## 1 Introduction

The current MPTCP implementation uses a congestion control algorithm called LIA, the "Linked-Increases" algorithm [4]. The design of LIA forces a tradeoff between optimal congestion balancing and responsiveness. Hence, to provide good responsiveness, LIA's current implementation must depart from optimal congestion balancing. This leads to important performance issues (refer to [5] and [6]): (i) in some scenarios upgrading TCP users to MPTCP results in a significant drop in the aggregate throughput in the network without any benefit for anybody; and (ii) MPTCP users can be excessively aggressive toward TCP users.

In this draft, we introduce OLIA, the "opportunistic linked increases algorithm", as an alternative to LIA. Contrary to LIA, OLIA's design is not based on a trade-off between responsiveness and optimal congestion balancing; it can provide both simultaneously [5].

Similarly to LIA, OLIA couples the additive increases and uses unmodified TCP behavior in the case of a loss. The difference between LIA and OLIA is in the increase part. OLIA's increase part, Equation (1), has two terms:

- The first term is an adaptation of the increase term of Kelly and Voice's algorithm [10]. This term is essential to provide optimal resource pooling.
- The second term guarantees responsiveness and non-flappiness of OLIA. By measuring the number of transmitted bytes since the last loss, it reacts to events within the current window and adapts to changes faster than the first term.

By adapting the window increases as a function of RTTs, OLIA also compensates for different RTTs. As OLIA is rooted on the optimal algorithm of [10], it provides fairness and optimal congestion balancing. Because of the second term, it is responsive and non-flappy.

OLIA is implemented in the Linux kernel and is now a part of UCLouvain's MPTCP implementation. In [5], we study the performance of MPTCP with OLIA over a testbed, by simulations and by theoretical analysis. We prove theoretically that OLIA is Pareto-optimal and that it satisfies the design goals of MPTCP described in [4]. Hence, it can provide optimal congestion balancing and fairness in the network. Our measurements and simulations indicate that MPTCP with OLIA is as responsive and non-flappy as MPTCP with LIA and that it solves the identified problems with LIA. Recent studies show that MPTCP with OLIA always outperforms MPTCP with LIA and is very responsive to the

changes in the environment [7, 8].

The rest of the document provides a description of OLIA. For an analysis of its performance, we refer to [5, 7, 8].

## 1.1 Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [1].

## 1.2 Terminology

**Regular TCP:** The standard version of TCP that operates between a single pair of IP addresses and ports [2].

**Multipath TCP:** A modified version of the regular TCP that allows a user to spread its traffic across multiple paths.

**MPTCP:** The proposal for multipath TCP specified in [3].

**LIA:** The Linked-Increases Algorithm of MPTCP (the congestion control of MPTCP) [4].

**OLIA:** The Opportunistic Linked-Increases Algorithm for MPTCP proposed in [5].

**all\_paths:** The set of all the paths established by the MPTCP connection.

**best\_paths:** The set of paths in all\_paths that are presumably the best paths for the MPTCP connection.

**max\_w\_paths:** The set of paths in all\_paths with largest congestion windows.

**collected\_paths:** The set of paths in all\_paths that are presumably the best paths but do not have largest congestion window (i.e. the paths of best\_paths that are not in max\_w\_paths).

**w\_r:** The congestion windows on a path r.

**rtt\_r:** The Round-Trip Time on a path r.

**MSS\_r:** The Maximum Segment Size that specifies the largest amount of data can be transmitted by a TCP packet on the path r.

## 2 The set of best paths, paths with maximum windows, and collected paths

A MPTCP connection has access to one or more paths. Let `all_paths` be the set of all the paths established by the MPTCP connection and `r` be one of these paths.

We denote by  $l_{1r}$  the number of bytes that were successfully transmitted over path `r` between the last two losses seen on `r`, and by  $l_{2r}$  the number of bytes that are successfully transmitted over `r` after the last loss. We denote by  $l_r = \max\{l_{1r}, l_{2r}\}$  the smoothed estimation of number of bytes transmitted on path `r` between last two losses.

$l_{1r}$  and  $l_{2r}$  can be measured by using information that is already available to a regular TCP user:

- For each ACK on `r`:  $l_{2r} \leftarrow l_{2r} + (\text{number of bytes that are acknowledged by ACK}),$
- For each loss on `r`:  $l_{1r} \leftarrow l_{2r}$  and  $l_{2r} \leftarrow 0.$

$l_{1r}$  and  $l_{2r}$  are initially set to zero when the connection is established. If no losses have been observed on `r` until now, then  $l_{1r}=0$  and  $l_{2r}$  is the total number of bytes transmitted on `r`.

Let  $rtt_r$  be the round-trip time observed on path `r` (e.g. the smoothed round-trip time used by regular TCP) and  $w_r$  be the congestion windows on path `r`. We denote by `best_paths` the set of paths `r` in `all_paths` that have the maximum value of  $l_r * l_r / rtt_r$ , by `max_w_paths` the set of paths `r` in `all_paths` with largest  $w_r$ , and by `collected_paths` the set of best paths that do not have maximum window size, i.e.:

- `best_paths = { r | r = arg max_{p in all_paths} (l_p * l_p / rtt_p) }`
- `max_w_paths = { r | r = arg max_{p in all_paths} (w_p) }`
- `collected_paths = { r | r in best_paths and not in max_w_paths }.`

where `arg max` is the argument of maximum, the set of points of the given argument for which the given function is maximum. `arg max` is applied over all paths `p` in `all_paths`.

`best_paths` represents the set of paths that are presumably the best paths (in term of transmission rate) for the user:  $1/l_r$  can be considered as an estimate of byte loss probability on path `r`, and hence the rate that path `r` can provide to a TCP user can be estimated by  $(2 * l_r)^{1/2} / rtt_r$ . A collected path is a path that is presumably

good but is not fully used. The set `collected_paths` can be empty.

Note that `l_{1r}`, `l_{2r}`, `l_r`, `rtt_r`, `w_r`, `best_paths`, `max_w_paths` and `collected_paths` are all functions of time.

### 3 Opportunistic Linked-Increases Algorithm

In this section, we introduce OLIA. OLIA is a window-based congestion-control algorithm. It couples the increase of congestion windows and uses unmodified TCP behavior in the case of a loss. OLIA is an alternative for LIA, the current congestion control of MPTCP.

The algorithm only applies to the increase part of the congestion avoidance phase. The fast retransmit and fast recovery algorithms, as well as the multiplicative decrease of the congestion avoidance phase, are the same as in TCP [2]. We also use a similar slow start algorithm as in TCP, with the modification that we set the ssthresh (slow start threshold) to be 1 MSS if multiple paths are established. In the case of a single path flow, we use the same minimum ssthresh as in TCP (i.e. 2 MSS). The purpose of this modification is to avoid transmitting unnecessary traffic over congested paths when multiple paths are available to a user.

For a path  $r$ , we denote by  $w_r$  the congestion windows on this path (also called subflow). We denote by  $MSS_r$  be the maximum segment size on the path  $r$ . We assume that  $w_r$  is maintained in bytes.

Our proposed "Opportunistic Linked-Increases Algorithm" (OLIA) must:

- For each ACK on path  $r$ , increase  $w_r$  by

$$\left( \frac{w_r / rtt_r^2}{(\text{SUM}_{\{p \text{ in all\_paths}\}} (w_p / rtt_p))^2} + \frac{\alpha_r}{w_r} \right) \quad (1)$$

multiplied by  $MSS_r * \text{bytes\_acked}$ .

The summation in the denominator of the first term is over all the paths  $p$  in `all_paths`. Recall that  $w_p$  and  $rtt_p$  denote the window size and the round trip time of a path  $p$ .

$\alpha_r$  is calculated as follows:

- If  $r$  is in `collected_paths`, then

$$\alpha_r = \frac{1/\text{number\_of\_paths}}{|\text{collected\_paths}|}$$

- If  $r$  is in `max_w_paths` and if `collected_paths` is not empty, then

$$\alpha_r = - \frac{1/\text{number\_of\_paths}}{|\text{max\_w\_paths}|}$$

- Otherwise,  $\alpha_r=0$ .

$|\text{collected\_paths}|$  and  $|\text{max\_w\_paths}|$  are the number of paths in  $\text{collected\_paths}$  and in  $\text{max\_w\_paths}$ . Note that the sum of all  $\alpha_r$  is equal to 0.

The first term in (1) is an adaptation of Kelly and Voice's increase term [10] and provides the optimal resource pooling (Kelly and Voice's algorithm is based on scalable TCP; the first term in (1) is a TCP compatible version of their algorithm that compensates also for different RTTs). The second term, with  $\alpha_r$ , guarantees responsiveness and non-flappiness of our algorithm.

By definition of  $\alpha_r$ , if all the best paths have the largest window size, then  $\alpha_r=0$  for any  $r$ . This is because we already use the capacity available to the user by using all the best path.

If there is any best path with a small window size, i.e. if  $\text{collected\_paths}$  is not empty, then  $\alpha_r$  is positive for all  $r$  in  $\text{collected\_paths}$  and negative for all  $r$  in  $\text{max\_w\_paths}$ . Hence, our algorithm increases windows faster on the paths that are presumably best but that have small windows. The increase will be slower on the paths with maximum windows. In this case, OLIA re-forwards traffic from fully used paths (i.e. paths in  $\text{max\_w\_paths}$ ) to paths that have free capacity available to the users (i.e. paths in  $\text{collected\_paths}$ ).

In [4], three goals have been proposed for the design of a practical multipath congestion control algorithm : (1) Improve throughput: a multipath TCP user should perform at least as well as a TCP user that uses the best path available to it. (2) Do no harm: a multipath TCP user should never take up more capacity from any of its paths than a TCP user. And (3) balance congestion: a multipath TCP algorithm should balance congestion in the network, subject to meeting the first two goals.

Our theoretical results in [5] show that OLIA fully satisfies these three goals. LIA, however, fails to fully satisfy the goal (3) as discussed in [5] and [6]. Moreover, in [5], we show through measurements and by simulation that our algorithm is as responsive and non-flappy as LIA and that it can solve the identified problems with LIA. In [7], Chen et al. study how MPTCP with LIA and OLIA performs in the wild with a common wireless environment, namely using both WiFi and Cellular simultaneously. Their results show that MPTCP with OLIA is very responsive to the changes in the environment and always outperforms MPTCP with LIA. Furthermore, using Experimental Design, Paasch et al. [8] show that MPTCP with OLIA satisfy the design goal of MPTCP in a very wide range of scenarios and always outperform MPTCP with LIA.



## 4 Practical considerations

Calculation of alpha requires performing costly floating point operation whenever an ACK received over path r. In practice, however, we can integrate calculation of alpha and Equation (1) together. Our algorithm can be therefore simplified as the following.

For each ACK on the path r:

- If r is in `collected_paths`, increase `w_r` by

$$\frac{w_r/rtt_r^2}{(\sum_p (w_p/rtt_p))^2} + \frac{1}{w_r * \text{number\_of\_paths} * |\text{collected\_paths}|} \quad (2)$$

multiplied by `MSS_r * bytes_acked`.

- If r is in `max_w_paths` and if `collected_paths` is not empty, increase `w_r` by

$$\frac{w_r/rtt_r^2}{(\sum_p (w_p/rtt_p))^2} - \frac{1}{w_r * \text{number\_of\_paths} * |\text{max\_w\_paths}|} \quad (3)$$

multiplied by `MSS_r * bytes_acked`.

- Otherwise, increase `w_r` by

$$\frac{(w_r/rtt_r^2)}{(\sum_p (w_p/rtt_p))^2} \quad (4)$$

multiplied by `MSS_r * bytes_acked`.

The summation in the dominator of the first term of equations (2), (3), and (4) is over the path p in `all_paths`. To compute the increase, we only need to determine the sets `collected_paths` and `max_w_paths` when an ACK is received on the path r. We can further simplify the algorithm by updating the sets `collected_paths` and `max_w_paths` only once per round-trip time or whenever there is a drop on the path.

We can see from above that in some cases (i.e. when r is `max_w_paths` and `collected_paths` is not empty) the increase could be negative. This is a property of our algorithm as in this case OLIA re-forwards traffic from paths in `max_w_paths` to paths in `collected_paths`. It is easy to show that using our algorithm,  $w_r \geq 1$  for any path r.

## 5 Discussion

Our results in [5] show that the identified problems with current MPTCP implementation are not due to the nature of a window-based multipath protocol, but rather to the design of LIA. OLIA shows that it is possible to build an alternative to LIA that mitigates these problems and that is as responsive and non-flappy as LIA.

Our proposed algorithm can provide similar resource pooling as Kelly and Voice's algorithm [10] and fully satisfies the design goals of MPTCP described in [4]. Hence, it can provide optimal congestion balancing and fairness in the network [5]. Moreover, it is as responsive and non-flappy as LIA and outperforms LIA in realistic scenarios such as wireless networks (refer to [5, 7, 8]).

We therefore believe that mptcp working group should revisit the congestion control part of MPTCP and that an alternative algorithm, such as OLIA, should be considered.

## 6 References

## 6.1 Normative References

- [2] Allman, M., Paxson, V., and E. Blanton, "TCP Congestion Control", RFC 5681, September 2009.
- [3] Ford, A., Raiciu, C., Greenhalgh, A., and M. Handley, "Architectural Guidelines for Multipath TCP Development", RFC 6182, March 2011.

## 6.2 Informative References

- [4] Raiciu, C., Handley, M., and D. Wischik, "Coupled Congestion Control for Multipath Transport Protocols", RFC 6356, October 2011.
- [5] R. Khalili, N. Gast, M. Popovic, U. Upadhyay, and J.-Y. Le Boudec. "MPTCP is not Pareto-optimality: Performance issues and a possible solution", ACM CoNEXT 2012 (The extended version of this paper is published at IEEE/ACM Transaction of Networking, volume 5, issue 25, October 2013).
- [6] R. Khalili, N. Gast, M. Popovic, and J.-Y. Le Boudec. "Performance Issues with MPTCP", draft-khalili-mptcp-performance-issues-05.
- [7] Chen Y.-C, Y.-S. Lim, R. J. Gibbens, E. M. Nahum, R. Khalili, and D. Towsley, "A Measurement-based Study of Multipath TCP Performance over Wireless Networks." ACM IMC 2013.
- [8] C. Paasch, R. Khalili, and O. Bonaventure, "On the Benefits of Applying Experimental Design to Improve Multipath TCP." ACM CoNEXT 2013.
- [9] UCL, Louvain-la-Neuve, Belgium, "MultiPath TCP-Linux kernel implementation," 2013 [Online]. Available: <http://mptcp.info.ucl.ac.be/>.
- [10] Kelly, F. and T. Voice, "Stability of end-to-end algorithms for joint routing and rate control", ACM SIGCOMM CCR vol. 35 num. 2, pp. 5-12, 2005.

## Authors' Addresses

Ramin Khalili  
T-Labs/TU-Berlin  
TEL 18, Ernst-Reuter-Platz 7  
10587 Berlin  
Germany

Phone: +49 30 8353 58276  
EMail: ramin@net.t-labs.tu-berlin.de

Nicolas Gast  
EPFL IC ISC LCA2  
Station 14  
CH-1015 Lausanne  
Switzerland

Phone: +41 21 693 1254  
EMail: nicolas.gast@epfl.ch

Miroslav Popovic  
EPFL IC ISC LCA2  
Station 14  
CH-1015 Lausanne  
Switzerland

Phone: +41 21 693 6466  
EMail: miroslav.popovic@epfl.ch

Jean-Yves Le Boudec  
EPFL IC ISC LCA2  
Station 14  
CH-1015 Lausanne  
Switzerland

Phone: +41 21 693 6631  
EMail: jean-yves.leboudec@epfl.ch